



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ :

A61B 5/04

A1

(11) International Publication Number:

WO 92/10134

(43) International Publication Date:

25 June 1992 (25.06.92)

(21) International Application Number: PCT/SE91/00822

(22) International Filing Date: 3 December 1991 (03.12.91)

(30) Priority data:
9003853-0


4 December 1990 (04.12.90) SE

(71)(72) Applicants and Inventors: KNUTSSON, Evert [SE/SE];
Lidskjaltsvägen 1 B, S-182 63 Djursholm (SE). GRANS-
BERG, Lennart [SE/SE]; Östbergavägen 12, S-182 63
Djursholm (SE).(74) Agents: BERG, Sven, Anders et al.; H. Albihs Patentbyrå
AB, Box 3137, S-103 62 Stockholm (SE).(81) Designated States: AT (European patent), AU, BE (Euro-
pean patent), CA, CH (European patent), DE (Euro-
pean patent), DK (European patent), ES (European pa-
tent), FR (European patent), GB (European patent), GR
(European patent), IT (European patent), JP, LU (Euro-
pean patent), MC (European patent), NL (European pa-
tent), SE (European patent), US.

Published

With international search report.

(54) Title: APPARATUS FOR MEASURING THE TRANSPORT TIME OF NERVE SIGNALS



(57) Abstract

The invention relates to apparatus which includes stimulating electrodes (2, 3) through which electrical signals are applied to an extremity of a patient (1). Detecting electrodes (30, 40) are disposed along the patient's spine and on the crown of the patient's head. The apparatus also includes signal amplifiers (7, 8), a loudspeaker (9) or the like to which an amplified signal is applied for physiological feedback purposes, an A/D-converter and a computer (20). Samples of signals are collected so as to obtain from the distributed electrodes means value curves from which the transport time of the nerve signals from respective extremities can be determined.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinea	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SN	Senegal
CI	Côte d'Ivoire	LJ	Liechtenstein	SU ⁺	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TG	Togo
DE [*]	Germany	MC	Monaco	US	United States of America
DK	Denmark				

⁺ Any designation of "SU" has effect in the Russian Federation. It is not yet known whether any such designation has effect in other States of the former Soviet Union.

Apparatus for Measuring the Transport Time of
Nerve Signals

5 The present invention relates to an apparatus of the kind defined in the preamble of Claim 1.

Such apparatus are known and used for diagnosing certain types of nerve damage. For example, it is usual to
10 apply electrical stimulating pulses to a heel of a patient with the patient lying flat on his stomach, and to measure the arrival time at the brain cortex, by attaching two electrodes to the skin of the crown of the patient's head, wherewith in the case of a normal person
15 a signal of the order of 0.5-3 μV will occur between the electrodes after a time lapse of 39.5 ± 3.3 ms from the time of administering the stimulating pulses. Although this signal contains a fair amount of noise, it is possible to obtain a summation signal from which the
20 transport time can be determined with the aid of graphic methods or the like, by adding together a large number of signals.

Endeavours have also been made to obtain a more complete
25 picture of the transport of the nerve signals, by positioning detectors along the spine, for instance so as to ascertain whether or not the function is influenced by defects in the spinal column. In this case, however, the disturbances which emanate from the muscles and the
30 heart are much more troublesome. In order to eliminate these disturbances, incisive methods have been attempted, in which electrodes are inserted into the vertebral canal. Endeavours to measure the transport time of nerve signals have also been made with a combination of
35 long measuring periods and patient relax periods, in which the patient is put to sleep or medicated. These

investigations, however, cannot be carried out in polyclinics and are expensive, time consuming and somewhat unpleasant for the patient.

5 The object of the invention is to provide apparatus which will enable measurements of this kind to be carried out and which will also enable the transport time of nerve impulses from an extremity of the patient to the cortex to be mapped within a short period of time
10 with the patient normally awake, so as to enable the investigation to be carried out in polyclinic facilities. There is a great need for investigations such as these, particularly in the case of patients suffering from back trouble and back pains, where it is known at
15 present that if the patient is put on the sick list and does not return to normal or rehabilitates within three months, the patient will become permanently unfit for work, in up to 90% of the cases involved. A quick diagnosis carried out in a polyclinic within a short space
20 of time is able to save the majority of these people and to return them to a normal life, by treating the patients adequately in time.

The object of the invention is achieved by means of
25 apparatus of the aforesaid kind having the characteristic features set forth in the characterizing clause of Claim 1. Preferred embodiments of the invention are defined in the depending Claims.

30 The most important problem solved by means of the present invention pertains to the signal to noise ratio in its widest meaning. Firstly, the signals are very small and are therefore subjected to normal noise. Secondly, artifacts exist, i.e. disturbances in the form of muscle
35 impulses for instance, EMG, which can reach up to $\pm 500 \mu V$, and impulses deriving from cardiac activity, ECG,

which can reach up to $\pm 2000 \mu V$, which shall be compared with the useful signals having an order of magnitude of only some μV .

5 These problems are far less troublesome when the signals are detected with the aid of electrodes placed on the crown of the patient's head, since only smaller artifacts are caused by the spontaneous activity of the cerebral cortex, EG, and to some extent by eye
10 movements.

According to the present invention, in addition to the electrodes placed on the patient's crown, electrodes can also be placed along the patient's spine so as to record
15 simultaneously response curves at different locations, e.g. from 4 to 9 or more spinal locations.

The aforesaid problem is solved in accordance with the invention through a combination of two different features, namely by reducing the "muscle signals" as a
20 result of making such signals audible to the patient through a loudspeaker (or through earphones or by visualizing said signals), so that the patient himself is able to reduce these signals and relax through an adaptive feedback, and by an effective weeding of the
25 signals with the aid of an appropriate algorithm so that only those signal sequences which appear to be relatively undisturbed are recorded and summated to provide mean curves.

30 Another difficulty is encountered when wishing to make a comparative investigation between the left and the right side of a patient. In conventional methods, first the one side is investigated and then the other. The result
35 is often unreliable, because of variations in excitability within the central nervous system.

Consequently, in accordance with one preferred embodiment of the invention, two sets of stimulating electrodes are attached to respective extremities, generally to the patient's heels, and activated alternately, the storage and processing of the resultant signals being effected in separate memory stores. It is suitable to activate the right extremity each alternate time and to activate the left extremity at times therebetween. In many cases, it may be suitable to attach one set of electrodes to a leg of the patient and the other set to an arm.

The invention will now be described in more detail on the basis of a non-limiting exemplifying embodiment thereof.

Figure 1 illustrates schematically an inventive apparatus connected to a patient.

Figure 2 illustrates a single recording of the nerve reaction as detected on the spine and on the crown of the patient over a period of 100 ms subsequent to administering a stimulating pulse.

Figure 3 illustrates mean value curves recorded at the same points as in Figure 1, although subsequent to establishing the mean value of 157 and 38 accepted recordings respectively.

Figure 4 illustrates the results obtained with complete measurement of the left side and the right side of a patient, recorded over a time of 15 minutes.

Figure 1 is a block schematic which illustrates the principal construction of the exemplifying inventive apparatus. Some of the blocks shown denote functions.

which are carried out in a computer 20, and consequently the Figure shall be read partially as a flowsheet.

5 A patient 1 lies flat on his stomach on a bed or like support surface, as comfortably as possible. Pairs of electrodes 2, 3 are attached conductively to the skin on the patient's heels. Similar electrodes are attached at 30 along the patient's spine and at 40 on the crown of the patient's head.

10 Connected to the electrodes 2, 3 are electric stimulators 4, 5, which may be of a conventional kind capable of delivering voltage pulses that can be adjusted between 100-200 V with durations of 0.1-0.5 ms, or current
15 pulses of 0-40 mA of the same durations. The stimulators are controlled by the computer 20 so as to deliver stimulation pulses at a pulse rate of 2-5 Hz. There are produced in this way nerve signals which pass up through the legs, into the nerve paths of the spinal cord and up
20 to the cortex. When arriving at respective locations along the spine, small potential variations in the skin occur, which can be detected successively via respective electrodes 30 and finally from the cortex through the electrodes 40. The electrodes 30 and 40 are connected,
25 via earth screened conductor pairs, to an insulated preamplifier 7 and a following final amplifier 8 with filters and variable amplification which is either adjusted manually or adjusted to suitable amplification levels by means of the computer, so as to obtain a range
30 suitable for receipt by a multiplex-operating A/D-converter. This converter may be a conventional 12-bit converter capable of detecting in time-multiplex all of the amplified signals, each having a sampling frequency of 2 kHz. Sampling begins at each stimulator pulse and
35 has a duration of 100 ms, so as to obtain for each "simultaneously" measured electrode a time-series of 200

values per shot.

Figure 1 also illustrates schematically the manner in which one of the signals arriving from the final amplifiers can be selected with the aid of an adjustable channel selector 10. This selected signal can be observed with the aid of a conventional oscilloscope 11 and passed to a loudspeaker 9, so that the patient is able to hear his own signals. Since muscle activations result in disturbances which dominate over the nerve signals, it is possible, by auditive feedback, to induce a concentrated patient to reduce this muscle activity, despite the fact that this muscle activity is not fully conscious or subjectively will-controlled. This is a surprisingly effective mechanism which contributes greatly to the good effect achieved by the present invention.

The output signals from the final amplifier 8 are passed to the A/D-converter where said signals are sampled. The sampled signals are selected with the aid of the computer 20, here drawn in the form of a box 13 and the mean values of the signals are formed in the box 14, and the results are successively displayed graphically on a screen 15. The boxes 6, 12, 13, 14 and 15 actually denote operations carried out by the computer, and consequently Figure 1 should be seen partially as a flowsheet explaining the connection between the electrodes affixed to the patient and the measuring processes carried out.

The recorded measurements are processed in the following manner, in accordance with a computer program:

- (1) Those series which present at least one value for which the A/D-converter has become saturated ("all

ones") are rejected.

(2) In order to obtain a first characteristic quality factor, or merit factor, there is calculated for respective series the sum of the absolute values of the differences between pairs of adjacent values, e.g. values having a mutual order difference of 4:

$$A = \sum |X_i - X_{i-4}| \quad 4 \leq 200$$

10

(3) In order to obtain a second characteristic quality factor, there is calculated in the same way the sum of the differences between pairs which lie at a greater distance apart, e.g. 40 units:

15

$$B = \sum |X_i - X_{i-40}| \quad 40 \leq 200$$

(4) In order to obtain a third characteristic quality factor, there is first calculated the maximum difference between two values separated by 4 samplings:

20

$$C = \max |X_i - X_{i-4}| \quad 4 \leq 200$$

In a first stage, 100 such series are recorded, for instance for each measuring signal which has not been rejected in accordance with (1) above. Thus, 100 value triads are obtained for these series. These can be seen as a shower of points in three-dimensional space laid in a space quadrant. These value triads are used to calculate a final criterion consisting of three numbers, such that, e.g., 25% of the 100 value triads satisfy this final criterion. For example, it is possible to calculate the mean value of each quality factor and to calculate the percentage thereof required for said rejection to be set to 25%

35

The actual measuring series begins when the first 100 series have been recorded and the triads stored. For each new measurement series of 200 values, the value triads are calculated and compared with the final criterion. If this criterion is satisfied by all three values, each of the 200 values is stored in its respective memory. Thus, successive accepted values are added together and ultimately there are obtained 200 mean values which when plotted form a curve which becomes progressively better and free from noise.

At the same time, the new value triad is recorded, while the first recorded value triad is discarded and a new final criterion is calculated. Thus, the final criterion is calculated in accordance with what can be called an iterative process which is adapted to prevailing conditions.

Figure 1 illustrates these operations schematically in the box 13, where selection and triad storage takes place, whereas the accepted series are stored during successive formation of mean values in the box 14. The mean values of the curves can then be viewed successively on a screen in the box 15, and when the curves are considered satisfactory, the measuring process can be interrupted and the result printed out. Thus, curves are obtained from several locations along the path travelled by the nerve signal to the cortex.

The following procedure is taken for eliminating noise and artifacts:

a) Slow variations are already eliminated in the final amplifier 8, through a high pass filter, e.g. a RC-filter having a limit frequency of 0.5 Hz.

- b) When the A/D-converter bottoms, the whole of the series being recorded at that time is rejected.
- c) Series having an excessively high frequency content are eliminated by the quality factor A.
- d) Series having excessive slow variations are eliminated by the quality factor B.
- e) Series with a large number of pronounced variations are eliminated by the quality factor C.

These rejection criteria can be varied in many ways. What is essential is that each individual value array is subjected to variation criteria and either accepted or rejected as a whole, whereas the accepted values are summated point by point to obtain the mean values.

With regard to the aforesaid adaptive, auditive feedback, this is effected by passing one of the signals most subjected to muscle disturbances, thus a signal obtained from a pair of the electrodes 30, suitably amplified, to a loudspeaker 9, through a channel selector 10. The same signal can also be sent to an oscilloscope 11, for visual monitoring purposes. In certain cases, instead of using a loudspeaker, it may be more appropriate to use headphones worn by the patient. In the case of deaf people, it is suitable to position the oscilloscope 11 so that it can be seen by the patient. It has been found that, in general, the patient is able to lie still over at least prolonged periods, so as to practically eliminate muscle disturbances as a disturbance source, especially in combination with the aforesaid disturbance elimination.

Figure 2 illustrates curves which are representative of

single recordings from one single stimulant, the upper curve being the curved obtained through the electrodes attached to the crown of the patient's head and the lower curve being the curve obtained with the electrodes attached to the patient's spine. Particular note should be paid to the mains disturbance of 50 Hz shown in the upper curve. The lower curve is greatly disturbed.

Figure 3 illustrates an early result obtained when practicing the invention. The upper curve shows a mean value obtained with the crown electrodes and the lower curve shows a mean value for the spine electrodes. In the former case, the curve indicates the mean value of 157 individual recordings, whereas the lower curve indicates the mean value of only 38 recordings made during the same time period. Thus, as would be expected, the rejection is much greater in the case of the spine signals, where the artifact frequency is high.

Figure 4 shows an example of an end result obtained when stimulating the right and the left legs of a male adult aged 20 years and having a height of 180 cm. In addition to crown electrodes, the uppermost curves, signals have been recorded from six different pairs of electrodes distributed along the patient's spine. The so-called latency, i.e. the time lapse from the time of stimulation to the time of receiving the signal has been measured primarily with respect to signal maximum, although with regard to the cortex also the more conventional minimum-based signal. The conventionally defined latency of 38 ms for the left side of the patient is normal for a person of that height, whereas the latency on the right side of the patient, 41 ms, shows an abnormal asymmetry. In accordance with the invention, other information is obtained in addition to the information gained from this result. It is seen that the latencies

of the spine signals for each pair on mutually opposite sides are similar, and consequently it is possible to exclude nerve damage downstream of these positions.

5

It is also of interest to note from a mathematical aspect that of all the thousands of curves accepted for the cortex in some cases less than one-third have been found acceptable in the upper part of the spine, whereas
10 the conditions are improved closer to the end of the spine. It will also be noted that it has been possible to record this set of curves in less than fifteen minutes.

Claims

1. Apparatus for measuring the transport time of nerve signals, the so-called latency, with an electrical
5 stimulance source intended for connection to an extremity of a patient, said apparatus including one or more electrodes for attachment to the patient's skin, amplifying means for amplifying electrical signals detected from respective electrodes and excited by said stimu-
10 lance source, and means for collecting and adding amplified signal sequences, each sequence commencing in dependence on a simultaneous signal collected from the stimulance source and having an electrical stimulance which acts on said extremity, c h a r a c t e r i z e d
15 by a plurality of electrode-pairs, each connected to a respective amplifying means and the output signals of which are applied to an A/D-converter through the control of a computer to which the stimulant-simultaneous signals are also applied; means for sampling in
20 time-multiplex through the A/D-converter and storing the output signals of said amplifying means in a memory store as numerical sequences at specific time points calculated from respective stimulant-simultaneous signals; means for weeding-out numerical sequences which
25 have a short time variation on average, a longer time variation on average and/or an absolute variation over a short time, which exceed quality factors calculated from earlier recorded number sequences; means for summing numbers in number sequences that remain subsequent to
30 said number-sequence weeding process and determining the mean values for those numbers which correspond to each of said specific time points, and means for signalling the output signals of said amplifying means to the patient's consciousness and awareness.

2. Apparatus according to Claim 1, c h a r a c -
t e r i z e d in that the means for signalling to the
patient's consciousness include a sound generator, such
as a loudspeaker or headphones.

5

3. Apparatus according to Claim 1, c h a r a c -
t e r i z e d in that the means for signalling to the
patient's consciousness include an image generator, such
as an oscilloscope.

10

4. Apparatus according to Claim 1, c h a r a c -
t e r i z e d in that the electrode pairs include an
electrode pair which is adapted for attachment to the
crown of the patient's head, and from 4 to 9 electrodes
for attachment along the patient's spine.

15

5. Apparatus according to Claim 1, c h a r a c -
t e r i z e d in that the apparatus includes two elec-
trical stimulance sources for attachment to two body
extremities; means for alternately applying electrical
stimulance thereto; and means for recording and storing
separately the output signals of said amplifying means
in accordance with their dependency on the stimulance of
one or the other of said body extremities.

20

1/3




FIG.1

2/3




FIG.2





FIG.3

3/3



INTERNATIONAL SEARCH REPORT

International Application No PCT/SE 91/00822

I. CLASSIFICATION OF SUBJECT MATTER (If several classification symbols apply, indicate all) ⁶ According to International Patent Classification (IPC) or to both National Classification and IPC IPC5: A 61 5/04																	
II. FIELDS SEARCHED <div style="text-align: center;">Minimum Documentation Searched⁷</div> <table style="width: 100%; border: none;"> <tr> <td style="width: 25%; border: 1px solid black; padding: 5px;">Classification System</td> <td style="border: none;"></td> <td style="width: 75%; border: 1px solid black; padding: 5px;">Classification Symbols</td> </tr> <tr> <td style="border: 1px solid black; padding: 5px; text-align: center;">IPC5</td> <td style="border: none;"></td> <td style="border: 1px solid black; padding: 5px; text-align: center;">A 61 B</td> </tr> </table> <div style="text-align: center; padding-top: 10px;">Documentation Searched other than Minimum Documentation to the Extent that such Documents are included in Fields Searched⁸</div> <p style="padding-top: 10px;">SE,DK,FI,NO classes as above</p>			Classification System		Classification Symbols	IPC5		A 61 B									
Classification System		Classification Symbols															
IPC5		A 61 B															
III. DOCUMENTS CONSIDERED TO BE RELEVANT⁹ <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 10%; padding: 5px;">Category¹⁰</th> <th style="width: 60%; padding: 5px;">Citation of Document,¹¹ with indication, where appropriate, of the relevant passages¹²</th> <th style="width: 30%; padding: 5px;">Relevant to Claim No.¹³</th> </tr> </thead> <tbody> <tr> <td style="text-align: center; vertical-align: top;">A</td> <td style="padding: 5px;">US, A, 3650264 (FRITS JACQUES JANSSEN) 21 March 1972, see the whole document ---</td> <td style="text-align: center; vertical-align: top;">1-2</td> </tr> <tr> <td style="text-align: center; vertical-align: top;">A</td> <td style="padding: 5px;">US, A, 4064870 (IONA F DUMITRESCU ET AL) 27 December 1977, see the whole document ---</td> <td style="text-align: center; vertical-align: top;">1,5</td> </tr> <tr> <td style="text-align: center; vertical-align: top;">A</td> <td style="padding: 5px;">US, A, 4570640 (JOHN E BARSA) 18 February 1986, see abstract; figure 10 ---</td> <td style="text-align: center; vertical-align: top;">1,4,5</td> </tr> <tr> <td style="text-align: center; vertical-align: top;">A</td> <td style="padding: 5px;">US, A, 4807643 (RANDY N ROSIER) 28 February 1989, see the whole document -----</td> <td style="text-align: center; vertical-align: top;">1,5</td> </tr> </tbody> </table>			Category ¹⁰	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³	A	US, A, 3650264 (FRITS JACQUES JANSSEN) 21 March 1972, see the whole document ---	1-2	A	US, A, 4064870 (IONA F DUMITRESCU ET AL) 27 December 1977, see the whole document ---	1,5	A	US, A, 4570640 (JOHN E BARSA) 18 February 1986, see abstract; figure 10 ---	1,4,5	A	US, A, 4807643 (RANDY N ROSIER) 28 February 1989, see the whole document -----	1,5
Category ¹⁰	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³															
A	US, A, 3650264 (FRITS JACQUES JANSSEN) 21 March 1972, see the whole document ---	1-2															
A	US, A, 4064870 (IONA F DUMITRESCU ET AL) 27 December 1977, see the whole document ---	1,5															
A	US, A, 4570640 (JOHN E BARSA) 18 February 1986, see abstract; figure 10 ---	1,4,5															
A	US, A, 4807643 (RANDY N ROSIER) 28 February 1989, see the whole document -----	1,5															
<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>¹⁰ Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 45%;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance, the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance, the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"A" document member of the same patent family</p> </div> </div>																	
IV. CERTIFICATION <table style="width: 100%; border: none;"> <tr> <td style="width: 50%; border: 1px solid black; padding: 5px;">Date of the Actual Completion of the International Search</td> <td style="width: 50%; border: 1px solid black; padding: 5px;">Date of Mailing of this International Search Report</td> </tr> <tr> <td style="border: 1px solid black; padding: 5px;">13th March 1992</td> <td style="border: 1px solid black; padding: 5px;">1992-03-16</td> </tr> <tr> <td style="border: 1px solid black; padding: 5px;">International Searching Authority</td> <td style="border: 1px solid black; padding: 5px;">Signature of Authorized Officer</td> </tr> <tr> <td style="border: 1px solid black; padding: 5px; text-align: center;">SWEDISH PATENT OFFICE</td> <td style="border: 1px solid black; padding: 5px; text-align: center;">ANDERS HOLMBERG</td> </tr> </table>			Date of the Actual Completion of the International Search	Date of Mailing of this International Search Report	13th March 1992	1992-03-16	International Searching Authority	Signature of Authorized Officer	SWEDISH PATENT OFFICE	ANDERS HOLMBERG							
Date of the Actual Completion of the International Search	Date of Mailing of this International Search Report																
13th March 1992	1992-03-16																
International Searching Authority	Signature of Authorized Officer																
SWEDISH PATENT OFFICE	ANDERS HOLMBERG																

**ANNEX TO THE INTERNATIONAL SEARCH REPORT
ON INTERNATIONAL PATENT APPLICATION NO. PCT/SE 91/00822**

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the Swedish Patent Office EDP file on 01/02/92. The Swedish Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A- 3650264	72-03-21	BE-A- 742546	70-06-02
		DE-A- 1960420	70-06-18
		FR-A- 2025238	70-09-04
		GB-A- 1241924	71-08-04
		NL-A- 6817326	70-06-08
		SE-B- 362198	73-12-03
US-A- 4064870	77-12-27	NONE	
US-A- 4570640	86-02-18	EP-A- 0236513	87-09-16
US-A- 4807643	89-02-28	NONE	

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.